## NSN 5935-00-917-5316

**Thread Class:** 

Right-hand
Body Style:
Straight shape
Overall Length:
0.880 inches
Overall Height:
0.620 inches

**Thread Direction:** 

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-917-5316

Overall Width:
0.280 inches
Environmental Protection:
Moisture resistant and vibration resistant
Distance Between Mounting Facility Centers:
0.625 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
14 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-14, sdg-f military specification single material response single mating end

## NSN 5935-00-917-5316

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:** 14 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.014 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Fiig: A039b0

Mil-m-14 spec.

Mil-std (military Standard):