

View Online at <https://aerobasegroup.com/nsn/5935-00-917-5386>

Bushing Diameter:

1.968 inches

Mounting Hole Circle Radius:

1.250 inches

Overall Diameter:

2.875 inches

Unthreaded Mounting Hole Diameter:

0.187 inches

Distance From Mounting Shoulder To Rear Face:

1.468 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

30.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end all contact groupings

Polarization Method:

Contact

Shell Type:

Armored

Connector Locking Method:

Contact twistlock

Terminal Location:

Back single mating end all contact groupings

Insert Material:

Plastic phenolic single mating end

Terminal Type:

Screw w/wire lock single mating end all contact groupings

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Insert Material Specification:

Mil-m-14, type cfg military specification single material response single mating end

Included Contact Quantity:

3 single mating end 2nd contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.