

View Online at <https://aerobasegroup.com/nsn/5935-00-917-5386>

**Bushing Diameter:**

1.968 inches

**Mounting Hole Circle Radius:**

1.250 inches

**Overall Diameter:**

2.875 inches

**Unthreaded Mounting Hole Diameter:**

0.187 inches

**Distance From Mounting Shoulder To Rear Face:**

1.468 inches

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

30.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

600.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

250.0 single mating end all contact groupings

**Polarization Method:**

Contact

**Shell Type:**

Armored

**Connector Locking Method:**

Contact twistlock

**Terminal Location:**

Back single mating end all contact groupings

**Insert Material:**

Plastic phenolic single mating end

**Terminal Type:**

Screw w/wire lock single mating end all contact groupings

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Nickel

**Insert Material Specification:**

Mil-m-14, type cfg military specification single material response single mating end

**Included Contact Quantity:**

3 single mating end 2nd contact grouping

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.