## NSN 5935-00-917-9635

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-917-9635 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated from panel **Identification Code Color:** Red **Body Style:** Threaded bushing mounted **Overall Length:** 0.734 inches **Mounting Bushing Length:** 0.484 inches **Body Length:** 0.734 inches **Overall Diameter:** 0.500 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 750.0 ac **Accommodated Finger Type:** Banana spring single finger **Finger Accommodation Diameter:** 0.170 inches single finger and 0.180 inches single finger **Finger Accommodation Length:** 0.562 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.312 inches **Capacitance In Picofarads: Thread Length:** 0.484 inches **Current Rating In Amps: Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi):

32 **Thread Size:** 

0.250 inches

## NSN 5935-00-917-9635

Tip Jack - Page 2 of 2



Terminal Type:
Tab, solder lug
Material:
Plastic, phenolic cap
Material:
Plastic phenolic cap
Surface Treatment:
Nickel terminal
Surface Treatment:
Nickel spring
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A03400