

View Online at <https://aerobasegroup.com/nsn/5935-00-917-9635>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Electrical Insulation Feature:**

Insulated from panel

**Identification Code Color:**

Red

**Body Style:**

Threaded bushing mounted

**Overall Length:**

0.734 inches

**Mounting Bushing Length:**

0.484 inches

**Body Length:**

0.734 inches

**Overall Diameter:**

0.500 inches

**Bushing Accommodation Hole Shape:**

Round

**Maximum Voltage Rating In Volts:**

750.0 ac

**Accommodated Finger Type:**

Banana spring single finger

**Finger Accommodation Diameter:**

0.170 inches single finger and 0.180 inches single finger

**Finger Accommodation Length:**

0.562 inches single finger

**Bushing Thru-hole Accommodation Diameter:**

0.312 inches

**Capacitance In Picofarads:**

4.0

**Thread Length:**

0.484 inches

**Current Rating In Amps:**

15.0

**Mounting Facility Type And Quantity:**

1 bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.250 inches

**Terminal Type:**

Tab, solder lug

**Material:**

Plastic, phenolic cap

**Material:**

Plastic phenolic cap

**Surface Treatment:**

Nickel terminal

**Surface Treatment:**

Nickel spring

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03400