
## NSN 5935-00-917-9635

Tip Jack - Page 1 of 2

**Thread Class:** 





2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated from panel **Identification Code Color:** Red **Body Style:** Threaded bushing mounted **Overall Length:** 0.734 inches Mounting Bushing Length: 0.484 inches **Body Length:** 0.734 inches **Overall Diameter:** 0.500 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 750.0 ac Accommodated Finger Type: Banana spring single finger **Finger Accommodation Diameter:** 0.170 inches single finger and 0.180 inches single finger **Finger Accommodation Length:** 0.562 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.312 inches Capacitance In Picofarads: 4.0 **Thread Length:** 0.484 inches **Current Rating In Amps:** 15.0 Mounting Facility Type And Quantity: 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches

## NSN 5935-00-917-9635

Tip Jack - Page 2 of 2



**Terminal Type:** 

Tab, solder lug

Material:

Plastic, phenolic cap

Material:

Plastic phenolic cap

Surface Treatment:

Nickel terminal

Surface Treatment:

Nickel spring

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03400