

View Online at <https://aerobasegroup.com/nsn/5935-00-918-4807>

**Body Style:**

Straight edge type

**Overall Length:**

Between 4.250 inches and 4.310 inches

**Overall Height:**

Between 0.328 inches and 0.358 inches

**Overall Width:**

Between 0.328 inches and 0.358 inches

**Environmental Protection:**

Moisture resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.145 inches

**Distance Between Mounting Facility Centers:**

Between 4.021 inches and 4.041 inches

**Board Accommodated Length:**

3.608 inches single board

**Board Accommodated Width:**

Between 0.054 inches and 0.070 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bridged contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Included Contact Quantity:**

22 single mating end single contact grouping

**Included Contact Type:**

Bifurcated spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.026 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A039b0