NSN 5935-00-919-2667

Electrical Receptacle Connector - Page 1 of 2



Thread Class: 2a and 2a Thread Direction: Right-hand and right-hand Body Style: Straight shape, external coupling Overall Length: 1.688 inches Overall Diameter: 0.812 inches Cable Entrance Diameter: 0.219 inches Mounting Facility Thickness: 0.281 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping Contact Material:	View Online at https://aerobasegroup.com/nsn/5935-00-919-2667	
Thread Direction: Right-hand and right-hand Body Style: Straight shape, external coupling Overall Length: 1.688 inches Overall Diameter: 0.812 inches Cable Entrance Diameter: 0.219 inches Mounting Facility Thickness: 0.281 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Thread Class:	
Right-hand and right-hand Body Style: Straight shape, external coupling Overall Length: 1.688 inches Overall Diameter: 0.812 inches Cable Entrance Diameter: 0.219 inches Mounting Facility Thickness: 0.281 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	2a and 2a	
Body Style: Straight shape, external coupling Overall Length: 1.688 inches Overall Diameter: 0.812 inches Cable Entrance Diameter: 0.219 inches Mounting Facility Thickness: 0.281 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Thread Direction:	
Straight shape, external coupling Overall Length: 1.688 inches Overall Diameter: 0.812 inches Cable Entrance Diameter: 0.219 inches Mounting Facility Thickness: 0.281 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Right-hand and right-hand	
Overall Length: 1.688 inches Overall Diameter: 0.812 inches Cable Entrance Diameter: 0.219 inches Mounting Facility Thickness: 0.281 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Body Style:	
Overall Diameter: 0.812 inches Cable Entrance Diameter: 0.219 inches Mounting Facility Thickness: 0.281 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Straight shape, external coupling	
Overall Diameter: 0.812 inches Cable Entrance Diameter: 0.219 inches Mounting Facility Thickness: 0.281 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Overall Length:	
Cable Entrance Diameter: 0.219 inches Mounting Facility Thickness: 0.281 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	1.688 inches	
Cable Entrance Diameter: 0.219 inches Mounting Facility Thickness: 0.281 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Overall Diameter:	
Mounting Facility Thickness: 0.281 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	0.812 inches	
Mounting Facility Thickness: 0.281 inches Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Cable Entrance Diameter:	
Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	0.219 inches	
Threaded Device Type: Coupling facility and mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Mounting Facility Thickness:	
Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	0.281 inches	
Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Threaded Device Type:	
Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Coupling facility and mounting bushing	
Contact Position Arrangement Style: N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Mating End Quantity:	
N single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	1	
Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Contact Position Arrangement Style:	
Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	N single mating end	
Shell Type: Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Contact Removability:	
Solid Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Nonremovable single mating end single contact grouping	
Connector Locking Method: Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Shell Type:	
Externally threaded shell Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Solid	
Connector Cable Strain Relief Method: Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Connector Locking Method:	
Compression nut Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Externally threaded shell	
Thread Size: 0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Connector Cable Strain Relief Method:	
0.625 inches and 0.625 inches Terminal Location: Back single mating end single contact grouping	Compression nut	
Terminal Location: Back single mating end single contact grouping	Thread Size:	
Back single mating end single contact grouping	0.625 inches and 0.625 inches	
	Terminal Location:	
Contact Material:	Back single mating end single contact grouping	
	Contact Material:	

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

NSN 5935-00-919-2667 Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Silver
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/double flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.001 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0