

View Online at <https://aerobasegroup.com/nsn/5935-00-919-4417>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape w/screw locks

Overall Length:

1.500 inches

Overall Height:

Between 0.860 inches and 0.930 inches

Overall Width:

0.340 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

26 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

48

Thread Size:

0.099 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

26 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.026 gold grains, troy and 0.026 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.