## NSN 5935-00-919-5835

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-919-5835

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

4.360 inches

**Overall Height:** 

0.406 inches

**Overall Width:** 

Between 0.333 inches and 0.353 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

0.116 inches

**Distance Between Mounting Facility Centers:** 

Between 4.024 inches and 4.040 inches

**Board Accommodated Length:** 

3.604 inches single board

**Board Accommodated Width:** 

Between 0.054 inches and 0.070 inches

**Mating End Quantity:** 

1

### **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:** 

Contact to contact polarizing keys

Shell Type:

Solid

#### **Terminal Location:**

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Shell Material:** 

Plastic diallyl phthalate

**Shell Surface Treatment Specification:** 

Mil-m-19833, ty gdi-30f military specification single treatment response

# NSN 5935-00-919-5835

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
44 single mating end single contact grouping
Included Contact Type:
Bifurcated spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.044 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-21097/1 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-19833 spec.