NSN 5935-00-920-3284

Plug-in Electronic Components Socket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-920-3284 **Body Material:** Plastic **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Top mount w/studs **Fabrication Method:** Molded **Overall Length:** 1.438 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 0.400 inches **Overall Height:** 0.594 inches **Overall Width:** 0.609 inches **Mounting Slot Width:** Between 0.138 inches and 0.146 inches **Body Mounting Hole Accommodation Length:** 1.000 inches **Body Mounting Hole Accommodation Width:** 0.641 inches **Distance Between Mounting Facility Centers:** 1.200 inches **Mounting Hole Style:** Rectangular, w/external slots **Specific Equipment Accommodated:** Relay **Contact Maximum Current Rating In Amps: Contact Material:** Phosphor bronze **Contact Surface Treatment:** Gold and silver **Accommodated Contact Quantity:** 14 **Thread Length:** 0.422 inches

Contact position

Polarization Type:

NSN 5935-00-920-3284

Plug-in Electronic Components Socket - Page 2 of 2



Projection Length Below Mounting Surface:
0.219 inches
Mounting Method:
Threaded stud
Mounting Type For Which Designed:
Chassis
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Contact Position Arrangement Style:
Symmetrical
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.014 gold grains, troy and 0.014 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Terminal Type And Quantity:
14 solder well
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A02300