

View Online at <https://aerobasegroup.com/nsn/5935-00-920-3528>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.250 inches

Overall Diameter:

1.000 inches

Environmental Protection:

Vibration resistant

Mounting Facility Thickness:

0.156 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Frequency Rating:

10000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

24 and 24

Thread Size:

0.688 inches and 0.688 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Triaxial socket single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces silver

Precious Material And Weight:

0.105 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0