

View Online at <https://aerobasegroup.com/nsn/5935-00-920-5299>

Body Material:

Plastic

Body Style:

Top or bottom mount w/molded saddle and bushing

Fabrication Method:

Molded

Overall Length:

1.281 inches

Temperature Rating:

-65.0 degrees celsius and 120.0 degrees celsius

Overall Height:

0.659 inches

Overall Width:

1.531 inches

Mounting Hole Diameter:

Between 0.213 inches and 0.223 inches

Body Mounting Hole Accommodation Diameter:

Between 1.321 inches and 1.341 inches

Mounting Hole Style:

Round, w/three mounting holes/slots

Specific Equipment Accommodated:

Relay

Contact Maximum Current Rating In Amps:

10.0

Contact Material:

Copper alloy

Contact Surface Treatment:

Gold

Accommodated Contact Quantity:

16

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 1.834 inches and 1.854 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 0.740 inches and 0.760 inches

Polarization Type:

Off center hole

Projection Length Above Mounting Surface:

Between 0.088 inches and 0.108 inches

Mounting Method:

Saddle

Mounting Type For Which Designed:

Chassis

Contact Position Arrangement Style:

Symmetrical

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.016 gold grains, troy

Precious Material:

Gold

Test Data Document:

96906-ms25462 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 tab, solder lug

Specification Data:

96906-ms25462 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02300