

View Online at <https://aerobasegroup.com/nsn/5935-00-920-6183>

Thread Class:

2b and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.844 inches

Overall Diameter:

0.250 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

0.519 inches

Mounting Facility Thickness:

0.093 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

C all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Current Rating In Amps:

1.5 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

400.0 all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thread Size:

0.312 inches and 0.312 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial socket 2nd mating end all contact groupings

Precious Material And Location:

Shell @surface gold

Precious Material And Weight:

0.100 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0