NSN 5935-00-921-4725

Electrical Plug Connector - Page 1 of 2



Electrical Flug Confidence - Fage 1 of 2
View Online at https://aerobasegroup.com/nsn/5935-00-921-4725
Body Style:
Angle shape w/cable clamp
Overall Diameter:
1.500 inches
Body Angle In Deg:
90.0
Environmental Protection:
Moisture resistant and vibration resistant and pressure proof
Cable Entrance Diameter:
0.406 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end single contact grouping
Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

NSN 5935-00-921-4725

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:

27 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.027 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0