Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-921-5609

Thread	Class:
i ili ouu	01400.

2a

**Thread Direction:** 

Right-hand

#### **Body Style:**

Straight shape, latching

#### **Overall Length:**

0.750 inches

#### **Overall Width:**

0.780 inches

#### Diameter:

0.780 inches

### **Environmental Protection:**

### Corrosion resistant

#### Threaded Device Type:

## Mounting bushing

## Mating End Quantity:

1

### **Contact Position Arrangement Style:**

Mh-5 single mating end

## Contact Removability:

Nonremovable single mating end single contact grouping

### Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

### **Polarization Method:**

Mating end

### **Connector Locking Method:**

Snap ring

### Thready Qty Per Inch (tpi):

20

# Thread Size:

0.500 inches

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate single mating end

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping



Terminal T	
Solder well	single mating end single contact grouping
Insert Mate	erial Specification:
Mil-p-19833	3, ty gdi-30 military specification single material response single mating end
Included C	Contact Quantity:
5 single ma	ting end single contact grouping
Bushing A	ccommodation Hole Shape:
Round	
Included C	Contact Type:
Round pin s	single mating end single contact grouping
Precious N	laterial And Location:
Contact sur	faces gold
Precious N	laterial And Weight:
0.005 gold	grains, troy
Precious N	faterial:
Gold	
Thread Se	ries Designator:
Unf	
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ation:
No	
Fiig:	
A039b0	
Mil-std (mi	litary Standard):
Mil-g-45204	1 spec