

View Online at <https://aerobasegroup.com/nsn/5935-00-921-8789>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

2.250 inches

**Overall Diameter:**

0.875 inches

**Environmental Protection:**

Fungus resistant and pressure proof and heat resistant and moisture resistant and thermal shock resistant and salt water resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Hn all mating ends

**Contact Removability:**

Removable all mating ends single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1000.0 all mating ends single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1000.0 all mating ends single contact grouping

**Contact Maximum Frequency Rating:**

9.0 kilohertz all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch and internally threaded coupling ring

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thread Size:**

0.750 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Insert Material:**

Plastic polystyrene all mating ends

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Included Contact Type:**

Coaxial pin all mating ends single contact grouping

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0