

View Online at <https://aerobasegroup.com/nsn/5935-00-921-8789>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

2.250 inches

Overall Diameter:

0.875 inches

Environmental Protection:

Fungus resistant and pressure proof and heat resistant and moisture resistant and thermal shock resistant and salt water resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Hn all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 all mating ends single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1000.0 all mating ends single contact grouping

Contact Maximum Frequency Rating:

9.0 kilohertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet latch and internally threaded coupling ring

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thread Size:

0.750 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Insert Material:

Plastic polystyrene all mating ends

Shell Material:

Copper alloy

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial pin all mating ends single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0