Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-922-1186

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, latching
Overall Length:
0.547 inches
Bushing Diameter:
0.375 inches
Overall Width:
0.625 inches
Diameter:
0.500 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
4 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
100.0 single mating end single contact grouping
Connector Locking Method:
Latching ring
Thread Length:
0.250 inches
Thready Qty Per Inch (tpi):
24
Thread Size:
0.375 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:

Plastic melamine single mating end

## NSN 5935-00-922-1186 Electrical Receptacle Connector - Page 2 of 2



Teri	minal Type:
Solo	der well single mating end single contact grouping
Incl	luded Contact Quantity:
4 sir	ngle mating end single contact grouping
Bus	shing Accommodation Hole Shape:
Rou	Ind
Incl	luded Contact Type:
Rou	and socket single mating end single contact grouping
Pre	cious Material And Location:
Con	ntact surfaces gold
Pre	cious Material And Weight:
0.00	04 gold grains, troy
Pre	cious Material:
Golo	d
Thr	ead Series Designator:
Unf	
She	elf Life:
N/a	
Uni	t Of Measure:
Den	nilitarization:
No	
Fiig	r.
A03	39b0