

View Online at <https://aerobasegroup.com/nsn/5935-00-922-2982>

**Body Style:**

Straight shape

**Overall Length:**

3.000 inches

**Overall Height:**

0.805 inches

**Overall Width:**

0.562 inches

**Environmental Protection:**

Shock resistant and vibration resistant and thermal shock resistant and humidity resistant and corrosion resistant

**Unthreaded Mounting Hole Diameter:**

0.205 inches

**Distance Between Mounting Facility Centers:**

2.500 inches

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

240.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Metal

**Shell Surface Treatment:**

Gold

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact and connector surfaces gold

**Precious Material And Weight:**

0.120 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0