## NSN 5935-00-922-2982

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-922-2982 **Body Style:** Straight shape **Overall Length:** 3.000 inches **Overall Height:** 0.805 inches **Overall Width:** 0.562 inches **Environmental Protection:** Shock resistant and vibration resistant and thermal shock resistant and humidity resistant and corrosion resistant **Unthreaded Mounting Hole Diameter:** 0.205 inches **Distance Between Mounting Facility Centers:** 2.500 inches **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 240.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** 

Gold

**Shell Surface Treatment:** 

Metal

# NSN 5935-00-922-2982

Electrical Receptacle Connector - Page 2 of 2



### **Included Contact Quantity:**

4 single mating end single contact grouping

#### **Included Contact Type:**

Coaxial socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact and connector surfaces gold

#### **Precious Material And Weight:**

0.120 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A039b0