# NSN 5935-00-922-3371

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-922-3371 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight edge type w/mounting flange **Overall Length:** 3.714 inches **Overall Height:** 0.687 inches **Overall Width:** 0.328 inches **Distance Between Mounting Facility Centers:** 3.406 inches **Board Accommodated Length:** 2.953 inches single board **Threaded Device Type:** Mounting hole **Board Accommodated Width:** Between 0.054 inches and 0.071 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys **Connector Locking Method:** Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping or copper single mating end single contact grouping

# NSN 5935-00-922-3371

Electrical Receptacle Connector - Page 2 of 2



| Insert | 1/1040 | امان |   |
|--------|--------|------|---|
| mserr  | WATE   | паі  | - |
|        |        |      |   |

Plastic diallyl phthalate single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Terminal Type:**

Tab, solder lug single mating end single contact grouping

#### **Insert Material Specification:**

Mil-p-19833, ty gdi-30f military specification single material response single mating end

#### **Included Contact Quantity:**

36 single mating end single contact grouping

#### **Included Contact Type:**

Bifurcated spring single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.036 gold grains, troy

#### **Precious Material:**

Gold

#### **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

### **Unit Of Measure:**

## **Demilitarization:**

No

## Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.