NSN 5935-00-922-3552

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-922-3552

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.218 inches

Cable Entrance Diameter:

0.156 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Compression nut

Thready Qty Per Inch (tpi):

28 and 28

Thread Size:

0.437 inches and 0.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-00-922-3552

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/double flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0