NSN 5935-00-922-4694

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-922-4694

Body Style: Straight shape w/flange **Overall Length:** 1.406 inches **Overall Height:** 1.703 inches **Overall Width:** 1.703 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.142 inches and 0.152 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.414 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.414 inches **Distance From Mounting Shoulder To Front Face:** Between 0.688 inches and 0.719 inches **Mating End Quantity: Contact Position Arrangement Style:** 24-61 all mating ends **Contact Removability:** Nonremovable all mating ends single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 all mating ends single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 270.0 Shell Type: **Connector Locking Method:** Bayonet pin **Contact Surface Treatment:** Gold all mating ends single contact grouping and copper all mating ends single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

NSN 5935-00-922-4694

Connector Adapter - Page 2 of 2

Fiig: A039b0



Included Contact Quantity:
61 2nd mating end single contact grouping
Included Contact Type:
Round socket 2nd mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.122 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-26482 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No