NSN 5935-00-923-0052

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-923-0052
Body Style:
Straight shape, flush mount
Overall Length:
0.984 inches
Overall Height:
1.687 inches
Overall Width:
3.375 inches
Unthreaded Mounting Hole Diameter:
0.138 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.875 inches
Distance From Mounting Shoulder To Front Face:
0.062 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
28 single mating end
Contact Removability:
Nonremovable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end 1st contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping and silver single mating end 1st contact grouping
Insert Material:
Plastic melamine single mating end or plastic phenolic single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end 1st contact grouping and qq-s-365 federal specification 2nd
treatment response single mating end 1st contact grouping
Criticality Code Justification:

Feat

NSN 5935-00-923-0052

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end 1st contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
15 single mating end 1st contact grouping
Included Contact Type:
Round socket single mating end 1st contact grouping
Special Features:
Contacts are omitted in positions 9, 11, 12, 13, 14, 16, 17, 22, 23, 24, 26, 27 and 28
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.015 gold grains, troy and 0.015 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.