NSN 5935-00-923-3626

Electrical Receptacle Connector - Page 1 of 2



Body Style: Straight shape, external coupling w/backshell Overall Length: 1.990 inches Overall Height: 1.390 inches Overall Width: 1.390 inches Environmental Protection: Moisture proof and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches
Overall Length: 1.990 inches Overall Height: 1.390 inches Overall Width: 1.390 inches Environmental Protection: Moisture proof and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.990 inches Overall Height: 1.390 inches Overall Width: 1.390 inches Environmental Protection: Moisture proof and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Overall Height: 1.390 inches Overall Width: 1.390 inches Environmental Protection: Moisture proof and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.390 inches Overall Width: 1.390 inches Environmental Protection: Moisture proof and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Overall Width: 1.390 inches Environmental Protection: Moisture proof and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.390 inches Environmental Protection: Moisture proof and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Environmental Protection: Moisture proof and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Moisture proof and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.062 inches
Distance From Mounting Shoulder To Front Face:
0.770 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
18-11 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Shell Type: Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-00-923-3626

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromium
Included Contact Quantity:
5 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Furnished items - grommet
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.025 silver grains, troy
Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0