Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-923-8390

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 2.250 inches |
| Distance From Mounting Shoulder To Front Face: |
| 1.062 inches |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| B4s single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Key, multiple key groove |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet latch |
| Thready Qty Per Inch (tpi): |
| 20 |
| Thread Size: |
| 0.937 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic epoxy single mating end |
| Included Contact Quantity: |
| 4 single mating end single contact grouping |
| Included Contact Type: |
| |
| Round socket single mating end single contact grouping |



Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.020 gold grains, troy Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0