

View Online at <https://aerobasegroup.com/nsn/5935-00-924-3890>

**Body Style:**

Straight shape threaded

**Overall Length:**

0.792 inches

**Overall Diameter:**

1.203 inches

**Environmental Protection:**

Hermetic and vibration resistant

**Distance From Mounting Shoulder To Front Face:**

0.605 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

18-24 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet shell

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Iron alloy 52 single mating end single contact grouping

**Insert Material:**

Glass single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Steel

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Included Contact Quantity:**

24 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Solder flange front mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0