Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-924-3890

Body Style:
Straight shape threaded
Overall Length:
0.792 inches
Overall Diameter:
1.203 inches
Environmental Protection:
Hermetic and vibration resistant
Distance From Mounting Shoulder To Front Face:
0.605 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
18-24 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet shell
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Iron alloy 52 single mating end single contact grouping
Insert Material:
Glass single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium

## NSN 5935-00-924-3890

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification: Qq-p-416 federal specification single treatment response Included Contact Quantity: 24 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Special Features:** Solder flange front mount Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0