## NSN 5935-00-924-4049

Electrical Receptacle Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-924-4049                          |
|--|
| Body Style:  |
| Straight shape, external coupling  |
| Overall Length:  |
| 1.222 inches   |
| Overall Height:  |
| 1.458 inches   |
| Overall Width:   |
| 1.458 inches   |
| Environmental Protection:  |
| Corrosion resistant and vibration resistant and shock resistant and moisture resistant |
| Unthreaded Mounting Hole Diameter:   |
| 0.120 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Height:              |
| 1.187 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:            |
| 1.187 inches   |
| Distance From Mounting Shoulder To Front Face:   |
| Between 0.510 inches and 0.557 inches  |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:  |
| 37p single mating end  |
| Contact Removability:  |
| Removable single mating end single contact grouping                                    |
| Contact Maximum Ac Voltage Rating In Volts:  |
| 600.0 single mating end single contact grouping  |
| Polarization Method:   |
| Key, multiple key groove   |
| Insert Position In Deg:  |
| 25.0   |
| Shell Type:  |
| Solid  |
| Connector Locking Method:  |
| Detent   |
| Terminal Location:   |
| Back single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Gold single mating end single contact grouping   |
| Terminal Tyne:   |

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

## NSN 5935-00-924-4049

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



| Shell Surface Treatment:   |
|--|
| Chromate and cadmium   |
| Shell Surface Treatment Specification:   |
| Qq-p-416, type 2, cl 3 federal specification single treatment response   |
| Included Contact Quantity:   |
| 37 single mating end single contact grouping   |
| Precious Material And Location:  |
| Contact surfaces gold  |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 81349-mil-c-81703 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 96906-ms3140 government standard   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |