NSN 5935-00-924-4246

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-924-4246 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.937 inches **Overall Diameter:** 1.330 inches **Environmental Protection:** Thermal shock resistant and salt water resistant and moisture resistant and sand resistant and hermetic **Distance From Mounting Shoulder To Front Face:** 0.692 inches **Mounting Facility Thickness:** 0.080 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 19-33 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1500.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 30.0 and 105.0 and 195.0 and 270.0 Shell Type: Solid **Connector Locking Method:** Detent **Thread Size:** 1.000 inches

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-00-924-4246

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
61 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0