NSN 5935-00-924-4445

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-924-4445
Body Style:
Hood, top opening w/clamp
Overall Length:
1.612 inches
Overall Height:
1.690 inches
Overall Width:
0.562 inches
Environmental Protection:
Corrosion resistant and pressure proof and humidity resistant and shock resistant and vibration resistant and cold resistant and heat resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
34 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
450.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Shell Type:
Hood, top opening
Connector Locking Method:
Friction
Connector Cable Strain Relief Method:
Cable clamp
Cable Opening Length:
0.612 inches
Cable Opening Width:
0.312 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:

Plastic diallyl phthalate and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping

NSN 5935-00-924-4445Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Insert Material Specification:
Mil-p-19833, ty gdi-30 military specification all material responses single mating end
Included Contact Quantity:
34 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.034 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.