## NSN 5935-00-924-4526

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-924-4526

**Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 1.690 inches and 1.710 inches **Overall Height:** Between 0.792 inches and 0.802 inches **Overall Width:** Between 0.355 inches and 0.365 inches **Distance Between Mounting Facility Centers:** Between 1.395 inches and 1.405 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 11 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Guide pin/socket **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Insert Material Specification:** Mil-m-19833, type gdi-30f military specification single material response single mating end **Included Contact Quantity:** 

10 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

## NSN 5935-00-924-4526

Electrical Receptacle Connector - Page 2 of 2



Special Features:
One terminal omitted
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
$0.010 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.010 \ \text{silver grains}, \ \text{troy}$
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-19833 spec.