NSN 5935-00-924-4916

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-924-4916

Body Style: Straight edge type **Overall Length:** 3.660 inches **Overall Height:** 0.458 inches **Overall Width:** 0.340 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Distance Between Mounting Facility Centers:** 3.406 inches **Board Accommodated Length:** 3.000 inches single board **Board Accommodated Width:** 0.054 inches **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Tab, solder lug single mating end single contact grouping **Included Contact Quantity:** 18 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

NSN 5935-00-924-4916

Electrical Receptacle Connector - Page 2 of 2



| Precious Material And Location: |
|---------------------------------|
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.018 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-g-45204 spec.