

View Online at <https://aerobasegroup.com/nsn/5935-00-925-6305>

Thread Class:

2a and 2g

Thread Direction:

Right-hand and left-hand

Body Style:

Rectangular shape center screwlock

Overall Length:

1.675 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.300 inches

Overall Height:

1.800 inches

Overall Width:

0.830 inches

Environmental Protection:

Thermal shock resistant and humidity resistant and shock resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.149 inches

Threaded Device Type:

Coupling facility and back shell

Mating End Quantity:

15

Contact Position Arrangement Style:

20 single mating end

Polarization Method:

Polarization boss and jackscrew

Connector Locking Method:

Jackscrew and jackscrew-socket

Thready Qty Per Inch (tpi):

32 and 56

Thread Size:

0.138 inches and 0.313 inches

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic epoxy single mating end or plastic phenolic single mating end

Insert Material Specification:

Mil-m-14, type sgd-f military specification all material responses single mating end or mil-p-19833, ty gdi-30f military specification all material responses single mating end

Special Features:

With mounting inserts

Thread Series Designator:

Unc and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.