

View Online at <https://aerobasegroup.com/nsn/5935-00-925-6305>

**Thread Class:**

2a and 2g

**Thread Direction:**

Right-hand and left-hand

**Body Style:**

Rectangular shape center screwlock

**Overall Length:**

1.675 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.300 inches

**Overall Height:**

1.800 inches

**Overall Width:**

0.830 inches

**Environmental Protection:**

Thermal shock resistant and humidity resistant and shock resistant and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.149 inches

**Threaded Device Type:**

Coupling facility and back shell

**Mating End Quantity:**

15

**Contact Position Arrangement Style:**

20 single mating end

**Polarization Method:**

Polarization boss and jackscrew

**Connector Locking Method:**

Jackscrew and jackscrew-socket

**Thready Qty Per Inch (tpi):**

32 and 56

**Thread Size:**

0.138 inches and 0.313 inches

**Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic epoxy single mating end or plastic phenolic single mating end

**Insert Material Specification:**

Mil-m-14, type sgd-f military specification all material responses single mating end or mil-p-19833, ty gdi-30f military specification all material responses single mating end

**Special Features:**

With mounting inserts

**Thread Series Designator:**

Unc and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.