NSN 5935-00-925-6308

Straight shape, internal coupling w/backshell

Thread Class: 2a and 2b

Body Style:

Overall Length: 1.531 inches

Overall Diameter:

Environmental Protection:

1.968 inches

Thread Direction:

Right-hand and right-hand

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-925-6308

Moisture resistant and vibration resistant and salt water resistant	
Threaded Device Type:	
Back shell and coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
28-21 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
22.0 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
500.0 single mating end single contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
700.0 single mating end single contact grouping	
Polarization Method:	
Key, multiple key groove	
Insert Position In Deg:	
220.0	
Shell Type:	
Solid	
Connector Locking Method:	
Internally threaded coupling ring	
Thready Qty Per Inch (tpi):	
18 and 18	
Thread Size:	
1.625 inches and 1.750 inches	
Terminal Location:	
Back single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping and silver single mating end single contact grouping	

NSN 5935-00-925-6308Electrical Plug Connector - Page 2 of 2



Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
$\ensuremath{Qq\text{-}p\text{-}416},\ \ensuremath{type}\ \ensuremath{2},\ \ensuremath{cl}\ \ensuremath{3}\ \ensuremath{federal}\ \ensuremath{specification}\ \ensuremath{single}\ \ensuremath{treatment}\ \ensuremath{response}\ \ensuremath{a}\ \ensuremath{cl}\ \ensuremath{a}\ \ensuremath{cl}\ \ensuremath{a}\ \ensuremath{cl}\ \ensuremath{a}\ \ensuremath{cl}\ \ensuremath{cl}\ \ensuremath{a}\ \ensuremath{cl}\ \ensuremat$
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.037 gold grains, troy and 0.037 silver grains, troy
Precious Material:
Gold and silver
Gold and silver
Gold and silver Thread Series Designator:
Gold and silver Thread Series Designator: Un and uns
Gold and silver Thread Series Designator: Un and uns Shelf Life:
Gold and silver Thread Series Designator: Un and uns Shelf Life: N/a
Gold and silver Thread Series Designator: Un and uns Shelf Life: N/a
Gold and silver Thread Series Designator: Un and uns Shelf Life: N/a Unit Of Measure:
Gold and silver Thread Series Designator: Un and uns Shelf Life: N/a Unit Of Measure: Demilitarization:
Gold and silver Thread Series Designator: Un and uns Shelf Life: N/a Unit Of Measure: Demilitarization: No
Gold and silver Thread Series Designator: Un and uns Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: