Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-925-8900

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
1.406 inches
Overall Diameter:
3.000 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Distance From Mounting Shoulder To Front Face:
1.094 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
40-62 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
16 and 16
Thread Size:
2.500 inches and 2.500 inches
Terminal Location:
Back single mating end single contact grouping



## **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416 type 2, cl 3 federal specification single treatment response **Included Contact Quantity:** 60 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.060 gold grains, troy and 0.060 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Un and un Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0