

NSN 5935-00-925-8983 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-925-8983 **Thread Class:** 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.790 inches **Overall Diameter:** 2.525 inches **Mounting Facility Thickness:** 0.250 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 1.750 inches and 1.188 inches

Terminal Location:

Back single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Insert Material Specification:

Mil-m-19833, ty gdi-30 military specification single material response single mating end

NSN 5935-00-925-8983

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

18 single mating end 2nd contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round pin single mating end 1st contact grouping

Thread Series Designator:

Double stub and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.