## NSN 5935-00-925-9106

**Thread Class:** 

**Thread Direction:** 

2a

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-925-9106



Right-hand **Body Style:** Straight shape **Overall Length:** 0.870 inches **Overall Height:** 0.530 inches **Overall Width:** 0.230 inches **Environmental Protection:** Vibration resistant **Distance Between Mounting Facility Centers:** 0.625 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 7 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy

## NSN 5935-00-925-9106

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

7 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Weight:** 

0.007 gold grains, troy

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.