NSN 5935-00-925-9170

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-925-9170 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.500 inches **Overall Height:** 0.531 inches **Overall Width:** 0.375 inches **Environmental Protection:** Pressure proof **Distance Between Mounting Facility Centers:** 1.408 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1350.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Jackscrew-socket Thread Length: 0.141 inches Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end and plastic diallyl isophthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-00-925-9170

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

44 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.