Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-925-9996

Thread Class:
2a
Za Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length: 1.250 inches
Overall Height: 0.578 inches
Overall Width:
0.391 inches
Distance Between Mounting Facility Centers:
Between 1.025 inches and 1.039 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1 Contact Desition American State
Contact Position Arrangement Style:
34 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
350.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thready Qty Per Inch (tpi):
56
Thread Size:
2.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping

## NSN 5935-00-925-9996

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification: Mil-m-14, type sdg-f military specification single material response single mating end **Included Contact Quantity:** 34 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.