# NSN 5935-00-926-0678

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-926-0678

Dody Chile
Body Style: Straight shape, external coupling
Overall Length:
1.266 inches
Overall Height:
1.453 inches
Overall Width:
1.453 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.969 inches
Distance From Mounting Shoulder To Front Face:
Between 0.462 inches and 0.493 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
16-26 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:

Cadmium

## NSN 5935-00-926-0678

Electrical Receptacle Connector - Page 2 of 2



#### **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

### **Included Contact Quantity:**

26 single mating end single contact grouping

### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Special Features:**

Four 0.150 in. Diameter intersected mtg holes spaced 1.125 in. By 1.125 in.

#### **Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-c-26482 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0