## NSN 5935-00-926-2930

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-926-2930

**Body Style:** 

Rectangular shape

**Overall Length:** 

2.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.687 inches

**Overall Height:** 

1.040 inches

**Overall Width:** 

1.000 inches

**Environmental Protection:** 

Shock proof and vibration resistant and salt water resistant

**Unthreaded Mounting Hole Diameter:** 

0.140 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.312 inches

**Mating End Quantity:** 

**Contact Position Arrangement Style:** 

18 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

13.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

18 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-00-926-2930

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.018 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-8384 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-8384 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0