## NSN 5935-00-926-2946

Telephone Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-926-2946 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Body Style:** Threaded bushing mounted long frame **Overall Length:** 3.172 inches **Overall Height:** 1.125 inches **Mounting Hole Diameter:** 0.156 inches **Mounting Bushing Length:** 0.375 inches **Body Width:** 0.562 inches **Bushing Accommodation Hole Shape:** Round **Accommodated Finger Type:** Two conductor, round tip single finger **Finger Accommodation Diameter:** 0.252 inches single finger **Finger Accommodation Length:** 1.015 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.375 inches **Jack Contact Arrangement Designator:** J7 **Mounting Facility Type And Quantity:** 1 bushing and 1 unthreaded hole Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.375 inches **Terminal Type:** Tab, solder lug

Material: Any acceptable spring **Surface Treatment:** Tin terminal

## NSN 5935-00-926-2946

Telephone Jack - Page 2 of 2



Surface Treatmer
------------------

Any acceptable contact

## **Test Data Document:**

81349-mil-j-641 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03400