Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-926-7417

Body Style:

Straight edge type w/mounting flange

Overall Length:

3.770 inches

Overall Height:

0.779 inches

Overall Width:

0.541 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

3.515 inches

Board Accommodated Length:

2.800 inches single board

Board Accommodated Width:

Between 0.086 inches and 0.103 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Inter-contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Copper single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-c-14550 military specification 1st treatment response single mating end single contact grouping and mil-g-45204 type 2, grade c military

specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder stud single mating end single contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14 ty sdg-f military specification single material response single mating end or mil-p-19833 ty gdi-301 military specification single material response single materi



Included Contact Quantity:

29 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.029 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-21097/4 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-c-14550 spec.