## NSN 5935-00-926-7420

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-926-7420

**Body Style:** 

Straight edge type

**Overall Length:** 

4.970 inches

**Overall Height:** 

0.453 inches

**Overall Width:** 

0.531 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

0.128 inches

**Distance Between Mounting Facility Centers:** 

Between 4.695 inches and 4.715 inches

**Board Accommodated Length:** 

3.395 inches single board and 4.005 inches single board

**Board Accommodated Width:** 

Between 0.054 inches and 0.070 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Contact to contact polarizing keys

Shell Type:

Solid

**Terminal Location:** 

Front single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Shell Material:** 

Plastic diallyl phthalate

**Included Contact Quantity:** 

41 single mating end single contact grouping

## NSN 5935-00-926-7420

A039b0

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Bifurcated spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.041 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-21097/34 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: