NSN 5935-00-926-7468

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-926-7468

View Online at https://aerobasegroup.com/nsn/5935-00-926-7468
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
1.969 inches
Overall Diameter:
1.391 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Cable Entrance Diameter:
0.734 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
18-32 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
138.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

32 single mating end single contact grouping

NSN 5935-00-926-7468

Mil-std (military Standard):

Mil-c-26482 spec.

Electrical Plug Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.032 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-26482 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
1030k0