NSN 5935-00-926-7590

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-926-7590

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Hood, top opening w/clamp
Overall Length:
1.250 inches
Overall Height:
2.063 inches
Overall Width:
0.344 inches
Cable Entrance Diameter:
Between 0.281 inches and 0.625 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
485.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Hood, top opening
Connector Locking Method:
Jackscrew-socket
Connector Cable Strain Relief Method:
Cable clamp
Thread Size:
0.099 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

NSN 5935-00-926-7590Electrical Plug Connector - Page 2 of 2



Insert Material:	
Plastic diallyl phthalate single mating end	
Terminal Type:	
Solder well single mating end single contact grouping	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Anodize	
Shell Surface Treatment Specification:	
Mil-a-8625, type 1 military specification single treatment response	
Insert Material Specification:	
Mil-m-19833, ty gdi-30-f military specification single material response single mating end	
Included Contact Quantity:	
20 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Precious Material And Location:	
Contact surface silver and contact surface silver	
Precious Material:	
Gold and silver	
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-m-19833 spec.	