NSN 5935-00-927-5278

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-927-5278

Thread Class: 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.000 inches and 1.031 inches **Overall Diameter:** 0.625 inches **Threaded Device Type:** Back shell and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 and 28 **Thread Size:** 0.190 inches and 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-b-626 federal specification single material response single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:**

Gold and copper

NSN 5935-00-927-5278

Electrical Receptacle Connector - Page 2 of 2



Shell Material Specification: Qq-b-626 federal specification single material response **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact @and body surfaces gold **Precious Material And Weight:** 0.105 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unf and unef Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No Fiig: A039b0